

THE PURELY LOGICAL CHOICE



**Purlogix**<sup>™</sup>

# Purlogix™

- Ultraviolet Bio-Film Control in Tank
- Safe function for hot dispense
- Internal filter mounting bracket with pre-drilled mounting locations for filtration assemblies
- Electronic hot and cold water dispense
- Sleek appliance appearance with raised dispense height
- Large dispense area for sport bottles and glasses
- High Capacity Stainless Cold Tank
- High Capacity Stainless hot tank
  - Primary and secondary floats
    - Electronic polymer body primary water shut off system
    - Mechanical float in tank secondary
- Adjustable leveling feet
- LED display panel
- Drip tray with knock out for drain
- Lifting handles
- Heavy gauge powder coated side panels
- Solid state circuit board with microprocessor control
- Adjustable cold control (3,5° to 8° C)
- Filtered Outlet for Coffee Brewer or Accessory Item
- 4 Phillips head screws access the entire unit
- Cold tank and hot tank drains
- Dealer adjustments possible
- Leak Detection with water Shut Off & Audio Alert [optional]

For maximum flexibility, Purlogix™ offers systems with RO, Micro Filtration or without filters. Optional In-Tank Ultraviolet [UV] Disinfection is available on all models.



## COUNTER TOP

MODELS		PCMV-1000e
INPUT VOLTAGE		220V AC, 50Hz
POWER CONSUMPTION	COMPRESSOR	100W
	HEATER	300W
TANK CAPACITY	COLD	4,5 L with 1,9 L Chilled
	HOT	1,5 L
FILTRATION SYSTEMS		Micro Filtration
DIMENSIONS		30cmW x 42cmD x 50,8cmH
WEIGHT		22,7 Kg

Includes In-Tank UV

## FLOOR-STANDING

MODELS		*PRV-2000e	*PMV-2000e	*PBV-2000e, PB-2000e
INPUT VOLTAGE		220V AC, 50Hz		
POWER CONSUMPTION	COMPRESSOR	100W		
	HEATER	460W		
TANK CAPACITY	COLD	5 L with 3 L Chilled		
	HOT	3 L		
FILTRATION SYSTEMS		80 GPD Reverse Osmosis	Sediment & Carbon MF	No System Installed
DIMENSIONS		30cmW x 42cmD x 125cmH		
WEIGHT		35 Kg	34 Kg	33 Kg

\*Includes In-Tank UV



THE PURELY LOGICAL CHOICE  
ULTRAVIOLET PROTECTION