



Inspirations®

Bottled Water &
Filtration (POU)
Dispenser

IB 210 NLEZ



IB 115



Features

- 2.0L stainless steel hot tank with all SS fittings between hot and cold tanks
- 3.8L polished stainless steel cold tank
- High quality, high output refrigeration and heating system
- R600a CARE® 10 reffridgerant
- Water is dispensed through industry standard Tomlinson style faucets that allow for Hot and Cold or Cook and Cold options
- Removable, two-piece drip tray for easy cleaning
- Easily converts to and from bottled water to filtration (POU)
- No external base plate
- Available in black (white, special order)
- Cup dispenser (option)
- Energy Star rated hot tank with On/Off switch
- CE listed
- **NoLeak® EZ-Fill®** – Patented no-spill adapter for use with no-spill bottle caps

Inspirations®

Bottled Water & Filtration (POU) Dispenser



Power

Voltage	220-240
Frequency (Hz)	50
Power Consumption	560W (+5% /-10%)
Cold Power Consumption	60W
Hot Power Consumption	450W
ES (kWh/24 hrs.)	0.87
% lower than ES Standard	8%

Hot Water System

Avg. Hot Water Temp at Nozzle @25°C Ambient (Cut-in / Cut-out Temp)	75.7°C +/- 5% / 86.5°C +/- 2%
Hot Water ARI Rating	37, 175ml > 74.9°C +/- 10%
Hot Thermometer / Heat Limiter	95°C +/- 3°C
Hot Thermostat / Thermistor Cycle	75°C +/- 5°C / 86°C +/- 2°C
Hot Water Flow Rate	1.4 LMP
Hot Tank Size (Litre)	2.0
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 23.9°C ambient (Cut-in / Cut-out Temp)	7°C + 2°C / -4°C
Cold Water ARI Rating	41, 147ml < 10°C +/- 10%
Cold Thermostat Set Point	7°C + 2°C / -4°C
Cold Water Flow Rate	2.1-2.5 LPM
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Litre)	3.78 / 2.08 / 1.51

Weights and Measurements

Net Weight (H&C / C&C Kgs)	13.2 / 14.6
Gross Weight (H&C / C&C Kgs)	14.5 / 15.9
Dispenser Dimensions / Boxed Dimensions WxDxH (cm)	31.5 x 35.5 x 111 / 32.7 x 35.6 x 113
Certifications	CE Listed Energy Star Rated